

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 29/11/2017 Version: 1.0

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : GRACEMATE POPPY - JASMIN

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Use of the substance/mixture : Air freshener

### 1.2.2. Uses advised against

No additional information available

### 1.3. Details of the supplier of the safety data sheet

TRUCK SHOP B.V.
De Corridor 12E
3621 ZB BREUKELEN - THE NETHERLANDS
T +31-346-284848
michel@truck-shop.nl

### 1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital, Guy's & St Thomas' Hospital Trust	Dudley Road B18 7QH Birmingham	0844 892 0111 (UK only, Monday to Friday, 08.00 to 18.00 hours)	

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2 H225

Full text of hazard classes and H-statements : see section 16

Adverse physicochemical, human health and environmental effects

Highly flammable liquid and vapour.

### 2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)

GHS02

Signal word (CLP) : Danger

Hazard statements (CLP) : H225 - Highly flammable liquid and vapour.

Precautionary statements (CLP) : P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames. No smoking.

P403+P235 - Store in a well-ventilated place. Keep cool.

P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation

# 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

## 3.2. Mixtures

29/11/2017 EN (English) 1/9

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Ethanol	(CAS-No.) 64-17-5 (EC-No.) 200-578-6 (EC Index-No.) 603-002-00-5 (REACH-no) 01-2119457610-43	25 - 45	Flam. Liq. 2, H225 Eye Irrit. 2, H319
Benzyl acetate	(CAS-No.) 140-11-4 (EC-No.) 205-399-7	1 - 3	Aquatic Chronic 3, H412
isopentyl acetate substance with a Community workplace exposure limit	(CAS-No.) 123-92-2 (EC-No.) 204-662-3 (EC Index-No.) 607-130-00-2	0,5 - 1	Flam. Liq. 3, H226
N-butyl acetate substance with a Community workplace exposure limit substance with national workplace exposure limit(s) (GB)	(CAS-No.) 123-86-4 (EC-No.) 204-658-1 (EC Index-No.) 607-025-00-1	0,01 - 0,1	Flam. Liq. 3, H226 STOT SE 3, H336
Ethyl acetate substance with a Community workplace exposure limit substance with national workplace exposure limit(s) (GB)	(CAS-No.) 141-78-6 (EC-No.) 205-500-4 (EC Index-No.) 607-022-00-5	0,01 - 0,1	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
1,3,4,6,7,8-hexahydro-4,6,6,7,8,8-hexamethylindeno[5,6-c]pyran, galaxolide, (HHCB)	(CAS-No.) 1222-05-5 (EC-No.) 214-946-9 (EC Index-No.) 603-212-00-7	0,05 - 0,1	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
isobutyl acetate substance with a Community workplace exposure limit substance with national workplace exposure limit(s) (GB)	(CAS-No.) 110-19-0 (EC-No.) 203-745-1 (EC Index-No.) 607-026-00-7	0,01 - 0,1	Flam. Liq. 2, H225 STOT SE 3, H336
benzyl benzoate	(CAS-No.) 120-51-4 (EC-No.) 204-402-9 (EC Index-No.) 607-085-00-9	0,01 - 0,1	Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 2, H411

#### Specific concentration limits:

Name	Product identifier	Specific concentration limits
Ethanol	(CAS-No.) 64-17-5 (EC-No.) 200-578-6 (EC Index-No.) 603-002-00-5 (REACH-no) 01-2119457610-43	(C >= 50) Eye Irrit. 2, H319

Full text of H-statements: see section 16

## **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

First-aid measures general

- : In all cases of doubt, or when symptoms persist, seek medical attention. If possible show this sheet, if not available show packaging or label.
- First-aid measures after inhalation
- : If you feel unwell, seek medical advice. Allow the victim to rest. Assure fresh air breathing. If symptoms persist call a doctor.
- First-aid measures after skin contact
- First-aid measures after eye contact
- : Wash skin with mild soap and water. If symptoms persist call a doctor.
- : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, consult an eye specialist.
- First-aid measures after ingestion
- : Never give anything by mouth to an unconscious person. Rinse mouth. Immediately call a POISON CENTER/doctor.

## 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : None to our knowledge.

## 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

Suitable extinguishing media : Water spray. dry chemical powder. Alcohol resistant foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.

## 5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapour.

Hazardous decomposition products in case of : During combustion: Toxic vapours may be released, Carbon oxides (CO, CO2).

5.3. Advice for firefighters

Precautionary measures fire : Keep upwind.

Firefighting instructions : Cool down the containers exposed to heat with a water spray. Contain the extinguishing fluids

by bunding. Do not discharge into drains or the environment.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Complete protective clothing. Self-contained breathing apparatus.

29/11/2017 EN (English) 2/9

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Ensure adequate ventilation. Remove all sources of ignition.

#### 6.1.1. For non-emergency personnel

Emergency procedures : Avoid contact with skin and eyes. Do not smoke. No flames, no sparks. Eliminate all sources of

ignition. In case of important spillage: Clear the danger area. Only qualified personnel

equipped with suitable protective equipment may intervene.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

## 6.2. Environmental precautions

Contain the spilled material by bunding. Do not allow product to spread into the environment.

### 6.3. Methods and material for containment and cleaning up

For containment : Stop leak without risks if possible. Absorb spillage with: Sand/earth. inert absorbent material.

Collect all waste in suitable and labelled containers and dispose according to local legislation.

Methods for cleaning up : Wash non-recoverable remainder with large amounts of water.

### 6.4. Reference to other sections

Concerning personal protective equipment to use, see section 8. Concerning disposal elimination after cleaning, see section 13.

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Precautions for safe handling

- : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Smoking is forbidden. No flames, no sparks. Eliminate all sources of ignition. Avoid the build-up of electrostatic charge. Use non-sparking tools. Ground/bond container and receiving equipment.
- : Do not drink, eat or smoke in the workplace. Always wash hands after handling the product. Keep away from food, drink and animal feeding stuffs.

## 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

Hygiene measures

- : Store in a cool, well-ventilated place. Keep container tightly closed. Keep away from open flames, hot surfaces and sources of ignition. Protect from heat and direct sunlight. Proper grounding procedures to avoid static electricity should be followed.
- Incompatible materials : Oxidation agents. Peroxides. Alkali metals. Alkaline earth metals. Magnesium. Aluminium.

## 7.3. Specific end use(s)

No additional information available

## **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

Ethanol (64-17-5)		
United Kingdom	Local name	Ethanol
United Kingdom	WEL TWA (mg/m³)	1920 mg/m <sup>3</sup>
United Kingdom	WEL TWA (ppm)	1000 ppm
isopentyl acetate (123-92-2)		
EU	Local name	Isopentylacetate
EU	IOELV TWA (mg/m³)	270 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	50 ppm
EU	IOELV STEL (mg/m³)	540 mg/m <sup>3</sup>
EU	IOELV STEL (ppm)	100 ppm
EU	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
N-butyl acetate (123-86-4)		
EU	Local name	n-butyl acetate
EU	Notes	(Ongoing)
EU	Regulatory reference	SCOEL Recommendations
United Kingdom	Local name	Butyl acetate
United Kingdom	WEL TWA (mg/m³)	724 mg/m <sup>3</sup>
United Kingdom	WEL TWA (ppm)	150 ppm
United Kingdom	WEL STEL (mg/m³)	966 mg/m³
United Kingdom	WEL STEL (ppm)	200 ppm
United Kingdom	Regulatory reference	EH40. HSE

29/11/2017 EN (English) 3/9

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Ethyl acetate (141-78-6)		
EU	Local name	Ethyl acetate
EU	IOELV TWA (mg/m³)	734 mg/m³
EU	IOELV TWA (ppm)	200 ppm
EU	IOELV STEL (mg/m³)	1468 mg/m <sup>3</sup>
EU	IOELV STEL (ppm)	400 ppm
EU	Regulatory reference	COMMISSION DIRECTIVE (EU) 2017/164
United Kingdom	Local name	Ethyl acetate
United Kingdom	WEL TWA (ppm)	200 ppm
United Kingdom	WEL STEL (ppm)	400 ppm
United Kingdom	Regulatory reference	EH40. HSE
isobutyl acetate (110-19-0)		
EU	Local name	Isobutyl acetate
EU	Notes	SCOEL Recommendations (Ongoing)
United Kingdom	Local name	Isobutyl acetate
United Kingdom	WEL TWA (mg/m³)	724 mg/m³
United Kingdom	WEL TWA (ppm)	150 ppm
United Kingdom	WEL STEL (mg/m³)	903 mg/m³
United Kingdom	WEL STEL (ppm)	187 ppm

### 8.2. Exposure controls

### Appropriate engineering controls:

Ensure good ventilation of the work station.

### Hand protection:

Chemical resistant gloves (according to European standard NF EN 374 or equivalent). Breakthrough time: refer to the recommendations of the supplier

# Eye protection:

If there is a risk of liquid being splashed: Safety glasses with side shields

## Respiratory protection:

If the ventilation is suitable, it is not essential to wear respiratory equipment

## **SECTION 9: Physical and chemical properties**

9.1. Information	on basic physical and chemical properties

Physical state : Liquid

Colour : No data available

Odour : jasmine.

Odour threshold : No data available pH : No data available Relative evaporation rate (butylacetate=1) : No data available Melting point : No data available Freezing point : No data available reezing point : No data available

Boiling point : > 35 °C (estimated value)

Flash point : 22 °C

: No data available Auto-ignition temperature Decomposition temperature : No data available Flammability (solid, gas) : Not applicable Vapour pressure : No data available : No data available Relative vapour density at 20 °C Relative density : No data available Solubility : No data available Log Pow : No data available : No data available Viscosity, kinematic Viscosity, dynamic : No data available

Explosive properties : Explosive vapour/air mixtures may be formed.

Oxidising properties : Non oxidizing material according to EC criteria.

29/11/2017 EN (English) 4/9

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Explosive limits : No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Highly flammable liquid and vapour.

### 10.2. Chemical stability

Stable at ambient temperature and under normal conditions of use.

### 10.3. Possibility of hazardous reactions

Flammable or explosive vapour/air mixtures may be formed.

### 10.4. Conditions to avoid

Heat. Heat sources. Direct sunlight. Avoid the build-up of electrostatic charge.

### 10.5. Incompatible materials

Respiratory or skin sensitisation

Germ cell mutagenicity

Reproductive toxicity

Carcinogenicity

Oxidizing agent. Peroxides. Alkali metals. Alkaline earth metals. Magnesium. Aluminium.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### **SECTION 11: Toxicological information**

Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	: Not classified (Based on available data, the classification criteria are not met)

Acute toxicity (dermai)	: Not classified (Based on available data, the classification criteria are not met)		
Acute toxicity (inhalation)	Not classified (Based on available data, the classification criteria are not met)		
Ethanol (64-17-5)			
LD50 oral rat	10470 mg/kg (95% Water) (OECD 401 method)		
LC50 inhalation rat	116,9 - 124,7 mg/l/4h (vapours) (equivalent or similar to OECD Guideline 403)		
isopentyl acetate (123-92-2)			
LD50 oral rat	16 <b>6</b> 00 mg/kg		
Benzyl acetate (140-11-4)			
LD50 oral rat	> 2000 mg/kg (OECD 401 method)		
LD50 dermal rabbit	> 5 <mark>000 mg/kg</mark>		
N-butyl acetate (123-86-4)			
LD50 oral rat	> 10000 mg/kg (equivalent or similar to OECD Guideline 423)		
LD50 dermal rabbit	> 14000 mg/kg (equivalent or similar to OECD Guideline 402)		
LC50 inhalation rat	> 21,1 mg/l/4h (OECD 403 method)		
Ethyl acetate (141-78-6)			
LD50 oral rat	4935 mg/kg		
LD50 dermal rabbit	> 18000 mg/kg		
LC50 inhalation rat	1600 mg/l/4h		
isobutyl acetate (110-19-0)			
LD50 oral rat	13413 mg/kg bodyweight (OECD 401 method)		
LD50 dermal rabbit	> 17400 mg/kg bodyweight (OECD 402 method)		
benzyl benzoate (120-51-4)			
LD50 oral rat	≈ 1430 mg/kg (OECD 401 method)		
LD50 dermal rabbit	> 2000 mg/kg		
1,3,4,6,7,8-hexahydro-4,6,6,7,8,8-hex	amethylindeno[5,6-c]pyran, galaxolide, (HHCB) (1222-05-5)		
LD50 oral rat	> 6500 mg/kg (OECD 401 method)		
LD50 dermal rat	> 10000 mg/kg (OECD 402 method)		
Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met)		
Serious eye damage/irritation	: Not classified (Based on available data, the classification criteria are not met)		

29/11/2017 EN (English) 5/9

: Not classified (Based on available data, the classification criteria are not met)

: Not classified (Based on available data, the classification criteria are not met)

: Not classified (Based on available data, the classification criteria are not met)

: Not classified (Based on available data, the classification criteria are not met)

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

STOT-single exposure	: !	Not classified (Based on available data, the classification criteria are not met)
STOT-repeated exposure	: 1	Not classified (Based on available data, the classification criteria are not met)

Ethanol (64-17-5)	
LOAEL (oral, rat, 90 days)	3156 mg/kg bodyweight/day
NOAEL (oral, rat, 90 days)	<= 1730 mg/kg bodyweight/day

Aspiration hazard : Not classified (Based on available data, the classification criteria are not met)

SECTION	12: Ecologic	cal informatio	n
SECTION	IZ. LCUIUGI	vai iiiiviiiiativ	

12 1	Toy	ricity

Ecology - general : To our knowledge, the product does not present any particular risk, under normal conditions of

use.

Acute aquatic toxicity : Not classified (Based on available data, the classification criteria are not met)
Chronic aquatic toxicity : Not classified (Based on available data, the classification criteria are not met)

Ethanol (64-17-5)	
LC50 fish	13500 - 15300 mg/l/96h (Pimephales promelas)
EC50 Daphnia	> 10000 mg/l/48h (Daphnia magna)
ErC50 (algae)	275 mg/l/72h (Chlorella vulgaris)
NOEC (chronic)	> 10 mg/l/ 21 d (Daphnia magna)
NOEC chronic algae	240 mg/l
Benzyl acetate (140-11-4)	

Benzyi acetate (140-11-4)	
LC50 fish	4 mg/l/96h (Oryzias latipes)
EC50 Daphnia	17 mg/l/48h (Daphnia magna) (OECD 202 method)
ErC50 (algae)	92 mg/l/72h (Desmodesmus subspicatus) (OECD 201 method)
N.I	_

it buty, about (120 co 1)		
LC50 fish	18 mg/l/96h (Pimephales promelas) (OECD 203 method)	
EC50 Daphnia	44 mg/l/48h (Daphnia Sp.)	
ErC50 (algae)	648 mg/l/72h (Scenedesmus subspicatus)	
NOEC chronic crustacea	23 mg/l/ 21 d (Daphnia magna) (OECD 211 method)	

Ethyl acetate (141-78-6)		
LC50 fish	230 mg/l/96h (Pimephales promelas)	
EC50 Daphnia	717 mg/l/48h (Daphnia magna)	
NOEC chronic crustacea	2,4 mg/l/ 21 d (Daphnia magna) (méthode OCDE 211)	
henzyl henzoate (120-51-4)		

benzyl benzoate (120-51-4)	WIRIII-K-SHIIPNI 🕖
LC50 fish	2,32 mg/l/96h (Danio rerio)
EC50 Daphnia	3,09 mg/l/48h (Daphnia magna) (OECD 202 method)
ErC50 (algae) 0,475 mg/l/72h (Selenastrum capricornutum, 96h) (OECD 201 method)	
1.3.4.6.7.8-hexahvdro-4.6.6.7.8.8-hexamethy	lindeno[5.6-c]pyran, galaxolide, (HHCB) (1222-05-5)

1,3,4,6,7,8-hexahydro-4,6,6,7,8,8-hexamethylindeno[5,6-c]pyran, galaxolide, (HHCB) (1222-05-5)			
LC50 fish 0,95 mg/l/96h (Oryzias latipes) (equivalent or similar to OECD Guideline 203)			
EC50 Daphnia	0,3 mg/l/48h (Daphnia magna) (méthode OCDE 202)		
ErC50 (algae)	> 0,854 mg/l/72h (Pseudokirchnerella subcapitata) (OECD 201 method)		
NOEC (acute)	0,201 mg/l/72h (Pseudokirchnerella subcapitata) (OECD 201 method)		
NOEC (chronic)	0,111 mg/l/ 21 d (Daphnia magna) (OECD 211 method)		

# 12.2. Persistence and degradability

Ethanol (64-17-5)				
Persistence and degradability Readily biodegradable. 70 % biodegradation. (20 days).				
Biochemical oxygen demand (BOD) 0,93 - 1,67 g O2/g substance				
Chemical oxygen demand (COD) 1,99 g O2/g substance				
N-butyl acetate (123-86-4)				
Persistence and degradability 83 % biodegradation (28 days). Readily biodegradable. (OECD 301D method).				
Ethyl acetate (141-78-6)				
Persistence and degradability 100 % biodegradation /28. days.				
1,3,4,6,7,8-hexahydro-4,6,6,7,8,8-hexamethylindeno[5,6-c]pyran, galaxolide, (HHCB) (1222-05-5)				
Chemical oxygen demand (COD) 3 g O2/g substance				

29/11/2017 EN (English) 6/9

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

## 12.3. Bioaccumulative potential

Ethanol (64-17-5)				
BCF	0,66			
Log Pow	-0,35 (20°C)			
Bioaccumulative potential	Not potentially bioaccumulable.			
N-butyl acetate (123-86-4)				
BCF	15,3			
Log Pow	2,3			
Ethyl acetate (141-78-6)				
Log Pow	0,73			
isobutyl acetate (110-19-0)				
Log Pow	2,3			
1 3 4 6 7 8-hevahydro-4 6 6 7 8 8-hevamethylindeno[5 6-c]nyran, galaxolide (HHCR) (1222-05-5)				

## 12.4. Mobility in soil

Log Pow

Ecology - soil Small adsorption	Product evaporates rapidly when in contact with the air.	7

### 12.5. Results of PBT and vPvB assessment

Component	
Ethanol (64-17-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
N-butyl acetate (123-86-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

### 12.6. Other adverse effects

No additional information available

# **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

Product/Packaging disposal recommendations : Conform to current legislation, regulations and orders.

5,3 (25°C)

# **SECTION 14: Transport information**

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID	
14.1. UN number	A VALVA VA V	DIIOV O	HADIH .	A	
1993	1993	1993	1993	1993	
14.2. UN proper shippi	ng name				
FLAMMABLE LIQUID, N.O.S. (Ethanol)	FLAMMABLE LIQUID, N.O.S. (Ethanol)	Flammable liquid, n.o.s. (Ethanol)	FLAMMABLE LIQUID, N.O.S. (Ethanol)	FLAMMABLE LIQUID, N.O.S. (Ethanol)	
14.3. Transport hazard	class(es)				
3	3	3	3	3	
3	3	3	3	3	
14.4. Packing group	14.4. Packing group				
II	II	II	Ш	II	
14.5. Environmental hazards					
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No	
No supplementary information available					

## 14.6. Special precautions for user

### - Overland transport

Classification code (ADR) : F1

Special provisions (ADR) : 274, 601, 640D

Limited quantities (ADR) : 11
Excepted quantities (ADR) : E2

29/11/2017 EN (English) 7/9

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Packing instructions (ADR) : P001, IBC02, R001

Mixed packing provisions (ADR) : MP19 Portable tank and bulk container instructions : T7

(ADR)

Portable tank and bulk container special

provisions (ADR)

: LGBF

: TP1, TP8, TP28

Tank code (ADR) Vehicle for tank carriage : FL : 2 Transport category (ADR) : S2, S20

Special provisions for carriage - Operation

(ADR)

: 33

: E2

Hazard identification number (Kemler No.)

Orange plates

33 1993

Tunnel restriction code (ADR) : D/E

## - Transport by sea

Special provisions (IMDG) : 274 : 1 L Limited quantities (IMDG) Excepted quantities (IMDG) : E2 : P001 Packing instructions (IMDG) : IBC02 IBC packing instructions (IMDG) Tank instructions (IMDG) : T7 TP1, TP8, TP28

Tank special provisions (IMDG)

: F-E EmS-No. (Fire) EmS-No. (Spillage) : S-E Stowage category (IMDG) : B MFAG-No 128

## - Air transport PCA Excepted quantities (IATA)

PCA Limited quantities (IATA) : Y341 PCA limited quantity max net quantity (IATA) : 1L PCA packing instructions (IATA) : 353 : 5L PCA max net quantity (IATA) CAO packing instructions (IATA) 364 60L

CAO max net quantity (IATA) Special provisions (IATA) : A3 ERG code (IATA) : 3H

## - Inland waterway transport

Classification code (ADN) : F1

: 274, 601, 640D Special provisions (ADN)

Limited quantities (ADN) : 1 L Excepted quantities (ADN) : E2 Carriage permitted (ADN) : T : PP, EX, A Equipment required (ADN)

: VE01 Ventilation (ADN) Number of blue cones/lights (ADN) : 1

## - Rail transport

Classification code (RID) : F1

Special provisions (RID) : 274, 601, 640D

Limited quantities (RID) : 1L Excepted quantities (RID)

Packing instructions (RID) : P001, IBC02, R001

Mixed packing provisions (RID) : MP19

29/11/2017 EN (English) 8/9

CK-SHOP.NL

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Portable tank and bulk container instructions : T

(RID)

Portable tank and bulk container special : TP1, TP8, TP28

provisions (RID)

Tank codes for RID tanks (RID) : LGBF
Transport category (RID) : 2
Colis express (express parcels) (RID) : CE7
Hazard identification number (RID) : 33

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## **SECTION 16: Other information**

Data sources : ECHA - European Chemicals Agency. SDS of suppliers.

Full text of H- and EUH-statements:

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4	
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1	
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1	
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2	
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
Flam. Liq. 2	Flammable liquids, Category 2	
Flam. Liq. 3	Flammable liquids, Category 3	
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis	
H225	Highly flammable liquid and vapour.	
H226	Flammable liquid and vapour.	
H302	Harmful if swallowed.	
H319 Causes serious eye irritation.		
H336 May cause drowsiness or dizziness.		
H400 Very toxic to aquatic life.		
H410 Very toxic to aquatic life with long lasting effects.		
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Flam. Liq. 2 H225 Expert judgment	
-----------------------------------	--

## SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

29/11/2017 EN (English) 9/9