

Aluminium-Gehäuse  
En-AW-6061

mit verschiedenen  
Verbundmaterialien und  
Beschichtung  
erhöht die Lebensdauer und  
schützt vor Umwelteinflüssen

# XMITTER Prime



Montageset  
Kabelsatz sowie  
Montagefüße  
sind in der  
Lieferung  
enthalten

"unzerbrechliche"  
Polycarbonat-Scheibe

verchromter  
Hintergrund



Optimiertes Gehäuse  
bessere Wärmeleitfähigkeit PDT-  
Technologie für ideale  
Betriebstemperatur  
Arbeitstemperatur von -40° bis +80°

5 Watt "CREE" LEDs  
"BIN" sortierte LEDs  
Lichtstreuung von 10° bis 65°  
stärkste LED-Scheinwerfer mit  
ECE-Zulassung von Vision X

# Chrome

Aluminum Enclosure  
En-AW-6061

with various composite  
materials and coating  
increases the service life and  
protects against environmental  
influences

# XMITTER Prime



## Mounting Set

Cable set as well  
as mounting feet  
are included in  
the delivery

"unbreakable"  
Polycarbonate lens

chromed  
Background



## Optimized Casing

better thermal conductivity PDT  
technology for ideal operating  
temperature  
Operating temperature from -40° to +80°

## 5 Watt "CREE" LEDs

"BIN" assorted LEDs light  
dispersion from 10° to 65°  
strongest LED headlights with  
ECE approval from VISION X.



# Chrome