

XMITTER Prime

Montageset
Kabelsatz sowie
Montagefüße sind
in der Lieferung
enthalten



Optimiertes Gehäuse
bessere Wärmeleitfähigkeit
PDT-Technologie für ideale
Betriebstemperatur
Arbeitstemperatur von -40° bis +80°

Aluminium-Gehäuse
En-AW-6061
mit verschiedenen
Verbundmaterialien und
Beschichtung
erhöht die Lebensdauer
und schützt vor
Umwelteinflüssen



"unzerbrechliche"
Polycarbonat-Scheibe

schwarzer Hintergrund

5 Watt "CREE" LEDs
"BIN" sortierte LEDs
Lichtstreuung von 10° bis 65°
stärkste LED-Scheinwerfer mit
ECE-Zulassung von Vision X



BLACK EDITION

XMITTER Prime

Mounting set
Cable set as well
as mounting feet
are included in
the delivery



Optimized casing
better thermal conductivity PDT
technology for ideal operating
temperature
Operating temperature from
-40° to +80°.

Aluminum housing
En-AW-6061
with various composite
materials and coating
increases the service life
and protects against
environmental influences



"unbreakable"
Polycarbonate lens

5 Watt "CREE" LEDs
"BIN" assorted LEDs light
dispersion from 10° to 65°
strongest LED headlights with
ECE approval from Vision X.

black Background



BLACK EDITION